



Installation and safety information

Handlebar ends for mirrors



**Indian Scout Bobber
from model year 2024**



Caution



Important safety information:

- Working on motorcycles poses a safety risk. Some work may only be carried out by appropriately qualified personnel. Faulty work can have serious consequences and may pose a threat to life and health. Only undertake installation works if you are sufficiently qualified and have an official workshop manual as well as all relevant service notifications available. Otherwise, we strongly recommend that the installation is carried out or at least checked in a workshop with appropriately trained personnel.
- When assembling, disassembling and tightening the torque of original parts, always proceed according to the workshop manual.
- All screws must be attached with thread-locking fluid. However, this should only be done after the installation is complete.
- It is your responsibility to check the product regularly and to determine if a service or replacement is required
- Please bear in mind that some products are safety-relevant parts of your vehicle. After a fall or collision, check the product and if there is the slightest indication of damage, you must completely replace it.
- This product is a component subject to registration.
- Some products require registration.
- These products have been designed for a standard vehicle. ABM® Fahrzeugtechnik GmbH makes no warranty or guarantee of any kind for any damages whatsoever arising out of the combination with other component parts not tested by ABM, as a consequence of improper installation or inadequate maintenance. The installation of other accessories (e.g. cases, bags, exhaust systems, etc.) from the vehicle manufacturer or other suppliers can impair the functionality of the product/vehicle and is therefore not permitted.

1 Preparation

Attention: The original bar-end mirrors cannot be used.

- Read the safety instructions and the assembly instructions completely and carefully.
- During the subsequent work, an unsafely positioned motorcycle can fall over. Therefore, make sure that the motorcycle is on firm, straight ground and is secured against falling over and rolling away.
- Keep children and pets away from the work area.
- Protect disassembled components from damage.
- When disassembling individual parts, pay attention to the screws with which they are attached. Keep these components and screws and, unless otherwise indicated, reuse them accordingly during assembly

2 Content



3 Assembly



Remove the original mirrors and handlebar ends.



Slide the new mirrors (clamp Ø 22 mm) onto the handlebar ends and mount them to the handlebars with the enclosed screws.

Then align and attach the mirrors.

Press the plastic lid onto the screw.



Caution: Make sure there is sufficient space between the mirror and the other parts (also with maximum steering angle).

4 Final check

- After completing the work, check that all components and screws are tight and functioning correctly. Also check the wheel's freewheel and the functionality of the brake system. Afterwards, a test drive must be done! After completing the test drive, the tightness of all screw connections must be checked, as well as the adequate freedom of access of all moving parts.